

ADMIX SB LATEX

SINGLE PART WHITE IN COLOUR ACRYLIC BASED POLYMER BONDING AGENT

PRODUCT

Single part, white emulsion, multi purpose acrylic based polymer bonding agent.

BENEFITS

Single pack, increases strength gaining, flexibility, excellent tensile strength, reduces shrinkage, prevent cement bleeding, outstanding water resistance, excellent adhesion, improves mechanical properties, abrasion resistant, reduces water permeability, improves workability and final strength, excellent bonding to concrete, steel and almost all construction materials, non-toxic and customer friendly. More economical than epoxy based bonding agents and can be used with potable water.

PACKING

Available in 1lt, 5lt, 50lt and 100lt plastic drums.

USES

ADMIX SB LATEX is a multi purpose additive and can be used with concrete and mortar for several benefits like excellent bonding, waterproofing characteristics, flexibility, workability, cohesiveness, early and ultimate strength gaining and for increasing durability.

For Concrete Repairs:

For repairs of damaged concrete areas like floors, beams, slabs or any other area, addition of ADMIX SB LATEX will provide excellent bonding, early and ultimate strength gain, abrasion and impact resistance, very good flexibility and workability.

ADMIX SB LATEX is recommended to be added in the concrete meant for water tanks, swimming pools, effluent tanks, lift pits, basement concrete etc., to get additional toughness and bonding characteristics required for water retaining structures.

ADMIX SB LATEX can also be used for bonding old concrete to new concrete as it is economical than epoxy based bonding agent.

ADMIX SB LATEX is strongly recommended for pressure grouting, to be added with cement at 5 lt per 50 kg cement for filling honeycombs effectively.

MIXING AND DOSAGE

ADMIX SB LATEX to be used along with water for easy and uniform distribution of chemical effect through out the depth of concrete.

Add ADMIX SB LATEX into the water and mix thoroughly. ADMIX SB LATEX mixed water to be added to the concrete / mortar to achieve required results.

For concrete repairs 200ml per one bag of cement, is recommended.

For bonding purposes (old concrete to new concrete), ADMIX SB LATEX to be brush applied. Surface should be saturated with water before applying this product.

SHELF LIFE

24 months from the date of manufacturing if stored in original container under shade.

ADDITION INFORMATION

A multi purpose additive for cement mixes, ADMIX SB LATEX plays a vital role in its action for providing a variety of benefits in repairs, concrete making and other applications like plastering and bonding. ADMIX SB LATEX is designed to become customer friendly product and it has no side effects.

QUALITY ASSURANCES

ADMIX SB LATEX is manufactured under stringent quality control, compatible with different climates of India.



No. 41, CCI House, 7th B Jakkur Cross, Opp: St.John's School, Amruthahalli, BANGALORE 560 092. Phone: (080) 23626333 . 23622421. Telefax No. (080) 23622421

Email : info@cciinc.in, sales@cciinc.in Website: www.cciinc.in

The information given in this data sheet is based on both current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we can not accept responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of the continuing research and development being under taken in our laboratory, we advise customers in their own interest to ensure that this data has not been superseded by a more up-to-date publication. Field services where provided, does not constitute supervisory responsibility. For additional information, CCI Inc local representative may be contacted.
