



ADMIX TILE ADHESIVE

SINGLE PART, THREE-IN-ONE, CERAMIC TILE ADHESIVE

PRODUCT

Single part, three-in-one, cement based, water proofing characteristics, ceramic tile adhesive, conforming to BS 5385-1976 part I Appendix-A.

BENEFITS

Better consistency, excellent adhesion, water proofing characteristics, easy to use, three-in-one compound. It can be used for floor tiles, wall tiles and tile-on-tile applications.

USES

ADMIX TILE ADHESIVE is specially designed and high quality product for the permanent fixing of floor tiles, wall tiles and tile-on-tile applications, both internal and external works.

APPLICATION GUIDE LINES

1. SURFACE PREPARATION

The surface should be sound and clean. All loose particles should be physically removed from the surface and the area of application should be kept slightly wet.

2. MIXING

ADMIX TILE ADHESIVE should be mixed with water at 3:1 ratio (3 kg powder & 1 Ltr water). However addition of can either be reduced or increased to achieve required consistency.

3. FIXING

The mixed ADMIX TILE ADHESIVE can be placed directly on the concrete surface and spread it to a uniform thickness of 3 to 4 mm. It can also be spread on concrete screeds, lime mortars and existing tiles.

4. FINISHING

Upon fixing the tiles, the protruding tile adhesive should be removed by using a wet cloth or sponge before it is set. Tile joints should be grouted after 24 hours of tile fixing.

PACKING

5 kgs & 25 kgs bags.

COVERAGE

25 kg ADMIX TILE ADHESIVE covers approximately 5-6 m² at 3 to 4mm thickness.

SHELF LIFE

6 months from the date of manufacturing.

QUALITY ASSURANCES

ADMIX TILE ADHESIVE is manufactured under stringent quality control compatible with different climates of India.



No. 41, CCI House, 7th B Jakkur Cross, Opp: St.John's School, Amruthahalli, BANGALORE 560 092. Phone: (080) 23626333 – 23622421. Telefax: (080)23622421.

Email : sales@cciinc.in info@cciinc.in website: www.cciinc.in

The information given in this data sheet is based on both current development work and many years of field experience. Whilst every effort is made to ensure that the information is reliable, we can not accept responsibility for any work carried out with our materials as we have no control over methods of application, site conditions etc. In view of the continuing research and development being undertaken in our laboratory, we advise customers in their own interest to ensure that this data has not been superseded by a more up-to-date publication. Field services where provided, does not constitute supervisory responsibility. For additional information, CCI Inc local representative may be contacted.
